

AC Digital Clamp Meters

MODEL 2017



- Tear drop shaped jaws for ease of use in tight places and crowded cable areas.
- Designed to meet internationally proven safety standards such as IEC 61010-1, UL3111 and VDE0411.
- Three functions in one unit; AC current, AC voltage and resistance.
- Resistance range provides audible continuity test.
- Frequency response from 40Hz to 1kHz on AC current and voltage ranges.



AC A	200/600A ±1.5%rdg±4dgt [50/60Hz] (200A) ±1%rdg±3dgt [50/60Hz] (600A) ±2%rdg±5dgt [45Hz - 1kHz]
AC V	200/600V ±1%rdg±2dgt [50/60Hz] ±1.5%rdg±4dgt [45Hz - 1kHz]
Ω	200Ω ±1.2%rdg±2dgt
Continuity buzzer	buzzer sounds below 30±20Ω
Conductor size	Ø33mm max.
Frequency response	45Hz - 1kHz
Safety Standard	IEC 61010-1 CAT III 600V Pollution Degree 2 IEC 61010-2-032
Power source	6F22 (9V) × 1
Dimensions	208(L) × 91(W) × 40(D)mm
Weight	400g approx.
Included Accessories	7066A (Test leads) 9079 (Carrying case) 6F22 × 1 Instruction Manual